

EMC TEST REPORT
for
Smart Team Holdings Limited

1W LED Charger Flashlight - High Capacity
Model No.: SZ-PP26650C

Prepared for : Smart Team Holdings Limited
Address : FLAT A01, 5/F., Great Wall Fty Bldg., 11 Cheung Shun Street,
Lai Chi Kwok, Kowloon, HK
Tel: 852 34286032
Fax: 852 34286033

Prepared by : Anbotek Compliance Laboratory Limited
Address : 1/F, 1/Building, SEC Industrial Park, No.4 Qianhai Road,
Nanshan District, Shenzhen, 518054, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772

Report Number : 201305723E
Date of Test : May 09~15, 2013
Date of Report : May 17, 2013

TABLE OF CONTENT

Description	Page
Test Report Verification	
1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility.....	5
1.3. Measurement Uncertainty.....	5
1.4. Test Summary.....	6
2. POWER LINE CONDUCTED EMISSION TEST.....	7
2.1. Block Diagram of Test Setup.....	7
2.2. Measuring Standard.....	7
2.3. Power Line Conducted Emission Limits.....	7
2.4. EUT Configuration on Measurement.....	7
2.5. Operating Condition of EUT.....	8
2.6. Test Procedure.....	8
2.7. Test Equipment.....	8
2.8. Measuring Results.....	8
3. RADIATED EMISSION TEST.....	11
3.1. Block Diagram of Test.....	11
3.2. Measuring Standard.....	11
3.3. Radiated Emission Limits.....	11
3.4. EUT Configuration on Test.....	12
3.5. Operating Condition of EUT.....	12
3.6. Test Procedure.....	12
3.7. Test Equipment.....	12
3.8. Measuring Results.....	12
4. ELECTROSTATIC DISCHARGE IMMUNITY TEST.....	17
4.1. Block Diagram of Test Setup.....	17
4.2. Measuring Standard.....	17
4.3. Severity Levels and Performance Criterion.....	17
4.4. EUT Configuration.....	18
4.5. Operating Condition of EUT.....	18
4.6. Test Procedure.....	18
4.7. Test Equipment.....	18
4.8. Measuring Results.....	18
5. RF FIELD STRENGTH SUSCEPTIBILITY TEST.....	20
5.1. Block Diagram of Test.....	20
5.2. Measuring Standard.....	20
5.3. Severity Levels and Performance Criterion.....	21
5.4. EUT Configuration on Test.....	21
5.5. Operating Condition of EUT.....	21
5.6. Test Procedure.....	21
5.7. Test Equipment.....	21
5.8. Measuring Results.....	22
6. PHOTOGRAPHS.....	24
6.1. Photo of Power Line Conducted Emission Test.....	24
6.2. Photo of Radiated Emission Test.....	24
6.3. Photo of Electrostatic Discharge Test.....	25
6.4. Photo of RF Field Strength susceptibility Test.....	26
APPENDIX I (Photos of the EUT) (3 Pages)	
APPENDIX II (CE Label) (1 Page)	

TEST REPORT VERIFICATION

Applicant : Smart Team Holdings Limited
Manufacturer : Shenzhen Smart Team Technology Ltd.
EUT : 1W LED Charger Flashlight - High Capacity
Model No. : SZ-PP26650C
Rating : Input: DC 5V, 900mA
Output: DC 5V, 1.0A
Trade Mark : ST

Measurement Procedure Used:

EN 55022: 2010;

EN 55024: 2010;

(IEC 61000-4-2: 2008; IEC 61000-4-3: 2006+A1 :2007+A2: 2010)

The device described above is tested by Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the EN 55022 and EN 55024 requirements. The Project in IEC 61000-4-3 was tested in Shenzhen EMTEK Co., Ltd.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Anbotek Compliance Laboratory Limited.

Date of Test : May 09~15, 2013

Prepared by :

Barak Ban

(Engineer/ Barak Ban)

Amy Ding

Reviewer :

(Project Manager/ Amy Ding)

Approved & Authorized Signer :

Tom Chen

(Manager/ Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : 1W LED Charger Flashlight - High Capacity

Model Number : SZ-PP26650C

Test Power Supply : DC 5V via USB Port/DC 5V

Applicant : Smart Team Holdings Limited
Address : FLAT A01, 5/F., Great Wall Fty Bldg., 11 Cheung Shun Street, Lai Chi Kwok, Kowloon, HK

Manufacturer : Shenzhen Smart Team Technology Ltd.
Address : Xutai Industrial Zone, Long Wo Road, Long Tian Village, Keng Zi Town, Longgang District, Shenzhen, Guangdong, China

Date of Receipt : May 09, 2013
Date of Test : May 09~15, 2013

1.2. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, August 20, 2010.

IC-Registration No.: 8058A-1

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, February 22, 2013.

CNAS - LAB Code: L3503

Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

Test Location

All Emissions tests were performed
Anbotek Compliance Laboratory Limited. at 1/F, 1/Building, SEC Industrial Park, No.4 Qianhai Road, Nanshan District, Shenzhen, 518054, China

1.3. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 4.3dB
Conduction Uncertainty	:	Uc = 3.4dB

1.4. Test Summary

For the EUT described above. The standards used were EN 55022 for Emissions & EN 55024 for Immunity.

Table 1 : Tests Carried Out Under EN 55022: 2010

Standard	Test Items	Status
EN 55022: 2010	Power Line Conducted Emission Test (150KHz To 30MHz)	√
EN 55022: 2010	Radiated Emission Test (30MHz To 1000MHz)	√


Table 2 : Tests Carried Out Under EN 55024: 2010

Standard	Test Items	Status
EN 55024: 2010	Electrostatic Discharge immunity Test	√
EN 55024: 2010	RF Field Strength susceptibility Test	√
EN 55024: 2010	Electrical Fast Transient/Burst Immunity Test	x
EN 55024: 2010	Surge Immunity Test	x
EN 55024: 2010	Injected Currents Susceptibility Test	x
EN 55024: 2010	Magnetic Field Susceptibility Test	x
EN 55024: 2010	Voltage Dips and Interruptions Test	x

- √ Indicates that the test is applicable
- x Indicates that the test is not applicable

2. POWER LINE CONDUCTED EMISSION TEST

2.1. Block Diagram of Test Setup



2.2. Measuring Standard

EN 55022: 2010

2.3. Power Line Conducted Emission Limits

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50 ~ 5.00	56.0	46.0
5.00 ~ 30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

2.4. EUT Configuration on Measurement

The following equipments are installed on Conducted Emission Measurement to meet EN 55022 requirements and operating in a manner which tends to maximize its emission characteristics in a normal application.

2.4.1. 1W LED Charger Flashlight - High Capacity

Model Number : SZ-PP26650C
Serial Number : N/A
Applicant : Smart Team Holdings Limited

2.5. Operating Condition of EUT

2.5.1. Setup the EUT as shown on Section 2.1.

2.5.2. Turn on the power of all equipments.

2.5.3. Let the EUT work in measuring mode (Charging to adapter) and measure it.

2.6. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and connected to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are investigated to find out the maximum conducted emission according to the EN 55022 regulations during conducted emission measurement.

The bandwidth of the test receiver (ESCI) is set at 9KHz in 150KHz~30MHz.

The frequency range from 150KHz to 30MHz is investigated for AC mains.

The test results are listed in Section 2.8.

2.7. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Nov. 12, 2012	1 Year
2.	LISN	SchwarzBeck	NSLK 8126	8126377	May 19, 2012	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	May 19, 2012	1 Year
4.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A

2.8. Measuring Results

PASS.


The frequency range 150KHz to 30MHz is investigated

The test curves are shown in the following pages.

CONDUCTED EMISSION TEST DATA

EUT: 1W LED Charger Flashlight - High Capacity M/N: SZ-PP26650C
 Operating Condition: Charging to adapter
 Test Site: 1# Shielded Room
 Operator: Finley Li
 Test Specification: DC 5V via USB Port
 Comment: N
 Tem: 22.2°C Hum: 60%

SCAN TABLE: "Voltage (150K~30M) FIN"
 Short Description: 150K-30M Disturbance Voltages



MEASUREMENT RESULT: "AT1305663102_fin"

5/13/2013 9:44PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.285000	41.80	20.1	61	18.9	QP	N	GND
0.465000	45.40	20.1	57	11.2	QP	N	GND
1.391500	41.90	20.2	56	14.1	QP	N	GND
3.070000	42.80	20.4	56	13.2	QP	N	GND
5.144500	36.50	20.5	60	23.5	QP	N	GND
13.289500	18.50	20.7	60	41.5	QP	N	GND

MEASUREMENT RESULT: "AT1305663102_fin2"


5/13/2013 9:44PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	36.20	20.1	55	18.9	AV	N	GND
0.289500	35.30	20.1	51	15.2	AV	N	GND
0.460500	36.40	20.1	47	10.3	AV	N	GND
1.441000	33.10	20.3	46	12.9	AV	N	GND
3.115000	32.30	20.4	46	13.7	AV	N	GND
5.176000	26.00	20.5	50	24.0	AV	N	GND

CONDUCTED EMISSION TEST DATA

EUT: 1W LED Charger Flashlight - High Capacity M/N: SZ-PP26650C
 Operating Condition: Charging to adapter
 Test Site: 1# Shielded Room
 Operator: Finley Li
 Test Specification: DC 5V via USB Port
 Comment: L
 Tem: 22.2°C Hum: 60%

SCAN TABLE: "Voltage (150K~30M) FIN"
 Short Description: 150K-30M Disturbance Voltages



MEASUREMENT RESULT: "AT1305663101_fin"

5/13/2013 9:41PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	46.30	20.1	65	18.8	QP	L1	GND
0.469500	37.70	20.1	57	18.8	QP	L1	GND
1.706500	33.40	20.3	56	22.6	QP	L1	GND
2.210500	33.40	20.3	56	22.6	QP	L1	GND
5.252500	29.80	20.5	60	30.2	QP	L1	GND
12.479500	15.60	20.7	60	44.4	QP	L1	GND

MEASUREMENT RESULT: "AT1305663101_fin2"

5/13/2013 9:41PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	29.70	20.1	55	25.4	AV	L1	GND
0.474000	25.40	20.1	46	21.0	AV	L1	GND
1.837000	24.60	20.3	46	21.4	AV	L1	GND
3.115000	24.70	20.4	46	21.3	AV	L1	GND
5.338000	19.10	20.5	50	30.9	AV	L1	GND
13.159000	7.40	20.7	50	42.6	AV	L1	GND

3. RADIATED EMISSION TEST


3.1. Block Diagram of Test

3.1.1. Block diagram of connection between the EUT and simulators

3.1.1.1 For Charging to adapter mode




3.1.1.2 For Discharging mode



(EUT: 1W LED Charger Flashlight - High Capacity)

3.1.2. Block diagram of test setup (In chamber)



(EUT: 1W LED Charger Flashlight - High Capacity)

3.2. Measuring Standard

EN 55022: 2010

3.3. Radiated Emission Limits

3.3.1. EN 55022: 2010

Radiated Emission Limits

All emanations from an EN 55022 device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below:

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMIT (dB μ V/m)
30 ~ 230	3	40
230 ~ 1000	3	47

- Note:
- (1) The smaller limit shall apply at the combination point between two frequency bands.
 - (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT.

3.4. EUT Configuration on Test

The EN 55022 regulations test method must be used to find the maximum emission during radiated emission measurement.

3.5. Operating Condition of EUT

3.5.1. Turn on the power.

3.5.2. Let the EUT work in test mode (Charging to adapter/Discharging) and measure it.

3.6. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Bilog antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the Receiver (ESCI) is set at 120kHz.

The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 3.8.

3.7. Test Equipment

The following test equipments are used during the radiated emission measurement:


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 12, 2012	1 Year
2.	Trilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	May 17, 2012	1 Year
3.	Pre-amplifier	Compliance Direction	PAP-0203	22008	May 19, 2012	1 Year
4.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A

3.8. Measuring Results

PASS.

The frequency range from 30MHz to 1000MHz is investigated.
The test curves are shown in the following pages.


Job No.:	AT1305663E	Polarization:	Vertical
Standard:	(RE)EN 55022_class B_3m	Power Source:	DC 5V via USB Port
Test item:	Radiation Test	Date:	2013/05/13
Temp.(C)/Hum.(%RH):	24.3(C)/55%RH	Time:	20:01:49
EUT:	1W LED Charger Flashlight - High Capacity	Test By:	Jimly Chen
Model:	SZ-PP26650C	Distance:	3m
Note:	Charging to adapter		



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	32.1795	50.65	-15.79	34.86	40.00	-5.14	QP	100	0	
2	39.5757	40.17	-10.70	29.47	40.00	-10.53	peak			
3	48.1626	44.41	-13.75	30.66	40.00	-9.34	peak			
4	97.1148	49.69	-15.91	33.78	40.00	-6.22	peak			
5	136.9391	50.95	-18.27	32.68	40.00	-7.32	peak			
6	186.4409	49.68	-16.25	33.43	40.00	-6.57	peak			


Job No.:	AT1305663E	Polarization:	Horizontal
Standard:	(RE)EN 55022_class B_3m	Power Source:	DC 5V via USB Port
Test item:	Radiation Test	Date:	2013/05/13
Temp.(C)/Hum.(%RH):	24.3(C)/55%RH	Time:	20:04:23
EUT:	1W LED Charger Flashlight - High Capacity	Test By:	Jimly Chen
Model:	SZ-PP26650C	Distance:	3m

Note: Charging to adapter



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	31.2893	37.69	-16.27	21.42	40.00	-18.58	peak			
2	37.9450	35.51	-11.99	23.52	40.00	-16.48	peak			
3	96.7749	42.45	-20.93	21.52	40.00	-18.48	peak			
4	148.4410	43.80	-23.36	20.44	40.00	-19.56	peak			
5	171.3926	53.91	-22.46	31.45	40.00	-8.55	peak			
6	349.2500	37.80	-14.00	23.80	47.00	-23.20	peak			


Job No.:	AT1305663E	Polarization:	Vertical
Standard:	(RE)EN 55022_class B_3m	Power Source:	DC 5V
Test item:	Radiation Test	Date:	2013/05/13
Temp.(C)/Hum.(%RH):	24.3(C)/55%RH	Time:	20:08:04
EUT:	1W LED Charger Flashlight - High Capacity	Test By:	Jimly Chen
Model:	SZ-PP26650C	Distance:	3m
Note:	Discharging		



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	38.8878	42.17	-11.24	30.93	40.00	-9.07	peak			
2	145.8611	51.65	-18.40	33.25	40.00	-6.75	QP	100	360	
3	193.7728	49.76	-15.90	33.86	40.00	-6.14	QP	100	0	
4	274.1939	47.59	-14.87	32.72	47.00	-14.28	peak			
5	334.8589	45.22	-13.54	31.68	47.00	-15.32	peak			
6	531.9635	40.15	-10.40	29.75	47.00	-17.25	peak			

Job No.:	AT1305663E	Polarization:	Horizontal
Standard:	(RE)EN 55022_class B_3m	Power Source:	DC 5V
Test item:	Radiation Test	Date:	2013/05/13
Temp.(C)/Hum.(%RH):	24.3(C)/55%RH	Time:	20:11:33
EUT:	1W LED Charger Flashlight - High Capacity	Test By:	Jimly Chen
Model:	SZ-PP26650C	Distance:	3m

Note: Discharging



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	150.0107	56.20	-23.34	32.86	40.00	-7.14	QP	100	0	
2	195.1365	57.09	-20.89	36.20	40.00	-3.80	QP	100	360	
3	275.1569	58.60	-18.41	40.19	47.00	-6.81	QP	100	0	
4	354.1831	55.52	-13.85	41.67	47.00	-5.33	QP	100	360	
5	511.8351	50.71	-10.99	39.72	47.00	-7.28	peak			
6	731.9202	41.69	-7.84	33.85	47.00	-13.15	peak			

4. ELECTROSTATIC DISCHARGE IMMUNITY TEST

4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators

4.1.1.1 For Charging to adapter mode




4.1.1.2 For Discharging mode



(EUT: 1W LED Charger Flashlight - High Capacity)

4.1.2. Block diagram of test setup



(EUT: 1W LED Charger Flashlight - High Capacity)

4.2. Measuring Standard

EN 55024: 2010

IEC 61000-4-2: 2008

Severity Level: 3 / Air Discharge: ± 8 kV Level: 2 / Contact Discharge: ± 4 kV

4.3. Severity Levels and Performance Criterion

4.3.1. Severity level

Level	Test Voltage Contact Discharge (kV)	Test Voltage Air Discharge (kV)
1.	± 2	± 2
2.	± 4	± 4
3.	± 6	± 8
4.	± 8	± 15
X	Special	Special

4.3.2. Performance criterion: **B**

4.4. EUT Configuration

The configuration of EUT are listed in Section 2.4.

4.5. Operating Condition of EUT

Same as conducted emission measurement, which is listed in Section 2.5 except the test set up replaced by Section 4.1.

4.6. Test Procedure

4.6.1. Air Discharge:

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 100 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed

4.6.2. Contact Discharge:

All the procedure shall be same as Section 4.6.1. except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

4.6.3. Indirect discharge for horizontal coupling plane

At least 50 single discharges shall be applied to the horizontal coupling plane, at points on each side of the EUT. The discharge electrode positions vertically at a distance of 0.1m from the EUT and with the discharge electrode touching the coupling plane.

4.6.4. Indirect discharge for vertical coupling plane

At least 50 single discharge shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

4.7. Test Equipment

The following test equipments are used during the electrostatic discharge immunity measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	ESD Simulators	KIKUSUI	KES4021	LJ003477	May 25, 2012	1 Year

4.8. Measuring Results

PASS

Please refer to the following page

Electrostatic Discharge Test Results

Anbotek Compliance Laboratory Limited


Applicant : Smart Team Holdings Limited	Test Date : May 14, 2013	
EUT : 1W LED Charger Flashlight - High Capacity	Temperature : 25°C	
M/N : SZ-PP26650C	Humidity : 54%	
Air discharge : ±8.0kV	Criterion : B	
Contact discharge: ±4.0kV	Test Engineer: Jimmy Zhou	
Test Mode : Charging to adapter/Discharging		
Location	Kind A-Air Discharge C-Contact Discharge	Result
Slot of the EUT 8 points	A	PASS
Others 6 points	A	PASS
USB Port 1 points	A	PASS
Metal surface of EUT 6 points	C	PASS
HCP 4 points	C	PASS
VCP of front 4 points	C	PASS
VCP of rear 4 points	C	PASS
VCP of left 4 points	C	PASS
VCP of right 4 points	C	PASS
Note:		

5. RF FIELD STRENGTH SUSCEPTIBILITY TEST

5.1. Block Diagram of Test

5.1.1. Block diagram of connection between the EUT and simulators

5.1.1.1 For Charging to adapter mode




5.1.1.2 For Discharging mode



(EUT: 1W LED Charger Flashlight - High Capacity)

5.1.2. Block diagram of RS test setup



(EUT: 1W LED Charger Flashlight - High Capacity)

5.2. Measuring Standard

EN 55024: 2010

IEC 61000-4-3: 2006+A1 :2007+A2: 2010

Severity Level: 2, 3V / m

5.3. Severity Levels and Performance Criterion

5.3.1. Severity Levels

Level	Field Strength V/m
1.	1
2.	3
3.	10
X	Special

5.3.2. Performance Criterion: A

5.4. EUT Configuration on Test

The configuration of the EUT is same as Section 2.4.

5.5. Operating Condition of EUT

Same as conducted emission measurement which is listed in Section 2.5. except the test setup replaced as Section 5.1.

5.6. Test Procedure

The EUT are placed on a table which is 0.8 meter high above the ground. The EUT is set 3 meters away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna are set on test. Each of the four sides of the EUT must be faced this transmitting antenna and measured individually.

In order to judge the EUT performance, a CCD camera is used to monitor its screen. All the scanning conditions are as following:

Condition of Test	Remark
1. Fielded Strength	3V/m (Severity Level 2)
2. Radiated Signal	Unmodulated
3. Scanning Frequency	80-1000MHz
4. Sweep time of radiated	0.0015 Decade/s
2. Dwell Time	1 Sec.

5.7. Test Equipment

The following test equipments are used during the RF Field Strength susceptibility measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	RF Power Meter. Dual Channel	BOONTON	4232A	10539	May 29, 2012	1 year

2.	50ohm Diode Power Sensor	BOONTON	51011EMC	34236/34238	May 29, 2012	1 year
3.	Broad-Band Horn Antenna	SCHWARZBECK	BBHA9120 L3F	332	May 29, 2012	1 year
4.	Power Amplifier	PRANA	AP32MT215	N/A	May 29, 2012	1 year
5.	Power Amplifier	MILMEGA	AS0102-55	N/A	May 29, 2012	1 year
6.	Signal Generator	AEROFLEX	2023B	N/A	May 29, 2012	1 year
7.	Field Strength Meter	HOLADAY	HI-6005	N/A	May 29, 2012	1 year
8.	RS232 Fiber Optic Modem	HOLADAY	HI-4413P	N/A	May 29, 2012	1 year
9.	Log.-Per. Antenna	SCHWARZBECK	VULP 9118E	N/A	May 29, 2012	1 year

5.8. Measuring Results

PASS.

Please refer to the following page.


6. PHOTOGRAPHS

6.1. Photo of Power Line Conducted Emission Test




6.2. Photo of Radiated Emission Test

Charging to adapter mode



Discharging mode



6.3. Photo of Electrostatic Discharge Test

Charging to adapter mode




Discharging mode



6.4 Photo of RF Field Strength susceptibility Test

Charging to adapter mode



Discharging mode



Anbotek

APPENDIX I
(Photos of EUT)

Anbotek

Figure 1
The EUT- Front View



Figure 2
The EUT- Back View



Figure 3
The EUT- Side View



Figure 4
The EUT- Inside View



Figure 5
PCB Of The EUT- Front View





Figure 6
PCB Of The EUT- Back View



**APPENDIX II
(CE Label)**

Anbotek

CE Label

1. The CE conformity marking must consist of the initials 'CE' taking the following form:
If the CE marking is reduced or enlarged, the proportions given in the above graduated drawing must be respected.
2. The CE marking must have a height of at least 5 mm except where this is not possible on account of the nature of the apparatus.
3. The CE marking must be affixed to the product or to its data plate. Additionally it must be affixed to the packaging, if any, and to the accompanying documents.
4. The CE marking must be affixed visibly, legibly and indelibly.
It must have the same height as the initials 'CE'

Proposed Label Location on EUT

EUT Back View/proposed CE Mark Location

