



CE EMC TEST REPORT

for

Smart Car Charger

MODEL: PCC2818

Trade Mark: N/A

Test Report Number: WSCT1511003307E

Issued Date: november 25, 2015

Issued for:

Smart Team Holdings Limited

**FLAT A 501,5/F,Great Wall Fty Bldy.,11 Cheung Shun St.,Lai Chi
Kok,Kowloon,HK**

Issued By:

WORLD STANDARDIZATION CERTIFICATION & TESTING CO., LTD.

**Building A, Baoshi Science & Technology Park, Baoshi Road,
Bao'an District, Shenzhen, Guangdong, China**

TEL: +86-755-26996192

FAX: +86-755-26996253



Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing CO., LTD. This document may be altered or revised by World Standardization Certification & Testing CO., LTD. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Revision History Of Report

Rev.	Issue No.	Revisions	Effect Page	Revised By
00	WSCT1511003307E	Initial Issue	ALL	Wang Fengbing





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

TABLE OF CONTENTS

1	TEST CERTIFICATION	4
2	TEST RESULT SUMMARY	5
3	EUT DESCRIPTION.....	6
4	TEST METHODOLOGY	7
4.1.	DECISION OF FINAL TEST MODE	7
4.2.	EUT SYSTEM OPERATION	7
5	SETUP OF EQUIPMENT UNDER TEST	8
5.1.	DESCRIPTION OF SUPPORT UNITS	8
5.2.	CONFIGURATION OF SYSTEM UNDER TEST	8
6	FACILITIES AND ACCREDITATIONS	9
6.1.	FACILITIES.....	9
6.2.	ACCREDITATIONS.....	9
6.3.	MEASUREMENT UNCERTAINTY	9
7	EMISSION TEST.....	10
7.1.	CONDUCTED EMISSION MEASUREMENT	10
7.2.	RADIATED EMISSION MEASUREMENT	13
7.3.	VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT	19
8	IMMUNITY TEST	21
8.1.	GENERAL DESCRIPTION.....	21
8.2.	GENERAL PERFORMANCE CRITERIA DESCRIPTION	22
8.3.	ELECTROSTATIC DISCHARGE (ESD).....	23
8.4.	RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD (RS)	27
8.5.	ELECTRICAL FAST TRANSIENT (EFT)	30
8.6.	SURGE IMMUNITY TEST.....	33
8.7.	CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)	36
8.8.	POWER FREQUENCY MAGNETIC FIELD.....	39
8.9.	VOLTAGE DIP & VOLTAGE INTERRUPTIONS	42
9	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	44
10	PHOTOGRAPHS OF EUT	46





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

1 TEST CERTIFICATION

Product: Smart Car Charger

Model: PCC2818

Applicant: Smart Team Holdings Limited
FLAT A 501,5/F,Great Wall Fty Bldy.,11 Cheung Shun St.,Lai Chi Kok,Kowloon,HK

Manufacturer: Shenzhen Smart Team Technology Limited
Xutai Industrial Zone,Long Wo Road, Long Tian Village,Keng Zi Town,Longgang District,Shenzhen ,Guangdong,China

Trade Mark: N/A

Tested: November 23, 2015 ~ November 24, 2015

Applicable Standards: EN 55022: 2010
EN61000-3-2:2014
EN61000-3-3:2013
EN 55024: 2010

Deviation from Applicable Standard
None

The above equipment has been tested by World Standardization Certification & Testing Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Abner Li
(Abner Li)

Date: 2015.11.25

Check By: Chen Hui
(Chen Hui)

Date: 2015.11.25



Approved By: Wang Fengbing
(Wang Fengbing)

Date: 2015.11.25





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

2 TEST RESULT SUMMARY

EMISSION			
Standard	Item	Result	Remarks
EN 55022:2010	Conducted	N/A	N/A
	Radiated	Below 1GHz	PASS
		Above 1GHz	N/A
EN 61000-3-2:2014	Harmonic current emissions	N/A	N/A
EN 61000-3-3:2013	Voltage fluctuations & flicker	N/A	N/A

IMMUNITY [EN 55024: 2010]			
Standard	Item		Result
EN 61000-4-2:2009	ESD		PASS
EN61000-4-3:2006+A1:2008 +A2:2010	Radiated, Radio-frequency, Electromagnetic field		PASS
EN 61000-4-4:2012	EFT	AC Mains	N/A
		DC/AC Supply	N/A
		RF Input	N/A
EN 61000-4-5:2006	Surge	AC Mains	N/A
		DC/AC Supply	N/A
		RF Input	N/A
EN 61000-4-6:2009	Conducted radio frequency disturbances	AC Mains	N/A
		DC/AC Supply	N/A
		RF Input	N/A
EN 61000-4-8: 2010	PFMF		N/A
EN 61000-4-11:2004	Voltage dips & voltage variations		N/A

Note:

1. N/A instead of not Applicable
2. The test result judgment is decided by the limit of test standard
3. The information of measurement uncertainty is available upon the customer's request.
4. Applicable only to EUT containing devices susceptible to magnetic fields, such as CRT monitors, Hall elements, electrodynamic microphones, magnetic field sensors, etc.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

3 EUT DESCRIPTION

Product	Smart Car Charger
Model	PCC2818
Trade Mark	N/A
Applicant	Smart Team Holdings Limited
Housing material	Plastic
EUT Type	<input checked="" type="checkbox"/> Engineering Sample. <input type="checkbox"/> Product Sample, <input type="checkbox"/> Mass Product Sample.
Serial Number	N/A
Power Rating	Input: 12V-24VDC 2A 22.5W Output: DC5V 2.25A*2
USB Line	N/A

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
USB	2	<input checked="" type="checkbox"/>





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

4 TEST METHODOLOGY

4.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the thereafter additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The following test mode(s) were scanned during the preliminary test:

Pre-Test Mode		Remark:
Conducted Emission	Mode: N/A	--
Radiated Emission	Mode: full loading	--

4.2. EUT SYSTEM OPERATION

1. Set up EUT with the support equipments.
2. Make sure the EUT work normally during the test.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	resistive load	N/A	N/A	N/A	N/A	N/A	Unshielded cable 1.0m
2	storage battery	N/A	N/A	N/A	N/A	N/A	Unshielded cable 1.0m

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST



(EUT: Smart Car Charger)





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at
Building A, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	TIMCO (The certificate registration number is Q2012033001)
Japan	VCCI (The certificate registration number is C-4128, R-3684, G-837)
Canada	INDUSTRY CANADA (The certificated registration number is 7700A-1)
Germany	TUV (The certificate registration number is UA50138086-0001,UA50138086-0002)
	EMCC (The certificated registration number is #080380)
	PHOENIX (The certificated registration number is 702777a)
	Eurofins
China	CNAS (The certificated registration number is L3732)
Switzerland	SGS (The certificated registration number is SZE0005409, SZE0005408)

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.wsct-cert.org>

6.3. MEASUREMENT UNCERTAINTY

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	+/- 3.20dB
Radiated emissions	Horizontal	30MHz ~ 230MHz
		230MHz ~1000MHz
		1000MHz~1800MHz
	Vertical	30MHz ~ 230MHz
		230MHz ~1000MHz
		1000MHz~1800MHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7 EMISSION TEST

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. LIMITS

(1) Limits of mains terminal disturbance voltage:

FREQUENCY (MHz)	LIMITS(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

(2) Limits of conducted common mode disturbance at telecommunication ports:

FREQUENCY (MHz)	Voltage Limits (dBμV)		Current Limits (dBμA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 – 0.5	84 to 74	74 to 64	40 to 30	30 to 20
0.5 – 30	74	64	30	20

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Shielding Room Test Site (843)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	100005	2016-08-18
LISN	AFJ	LS16	16010222119	2016-08-18
LISN(EUT)	Mestec	AN3016	04/10040	2016-08-18

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.
2. N.C.R = No Calibration Request.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.1.3. TEST PROCEDURES

Procedure of Preliminary Test

The EUT and Support equipment, if needed, was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per EN55022 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

All I/O cables were positioned to simulate typical actual usage as per EN55022.

The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in Item 3.1 were scanned during the preliminary test.

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level.

The EUT configuration and cable configuration of the above highest emission levels were recorded for reference of the final test.

Procedure of Final Test

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.


The test data of the worst-case condition(s) was recorded.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.1.5. TEST RESULTS

Model No.	PCC2818	6dB Bandwidth	9 KHz
Environmental Conditions	22°C, 55% RH	Test Mode	N/A
Detector Function	Peak / Quasi-peak/AV	Test Result	N/A
Test By	Abner Li		

NOTE:

L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

“---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Attenuator factor + Cable loss

Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Level (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

EUT is powered by storage battery, does not apply to the test project.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.2. RADIATED EMISSION MEASUREMENT

7.2.1. LIMITS

FREQUENCY (MHz)	dB μ V/m (At 3m)
	Limit
30 ~ 230	40
230 ~ 1000	47

Frequency range (MHz)	Average Limit (dB μ V/m)	Peak Limit (dB μ V/m)
1000 ~ 3000	50	70
3000 ~ 6000	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dB μ V/m) = 20 log Emission level (μ V/m).

7.2.2. TEST INSTRUMENTS

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	100005	2016-08-18
Spectrum Analyzer	R&S	FSU	100114	2016-08-18
Pre Amplifier	H.P.	HP8447E	2945A02715	2016-08-18
Pre Amplifier	H.P.	PAP-1G18-38	7621	2016-08-18
Bilog Antenna	SUNOL Sciences	JB5	A021907	2016-09-13
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	2016-09-13
HORN ANTENNA	COMPLIANCE ENGINEERING	CE18000	--	2016-09-13
System-Controller	CCS	N/A	N/A	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.

2. N.C.R = No Calibration Request.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.2.3. TEST PROCEDURE

Procedure of Preliminary Test

The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

Support equipment, if needed, was placed as per EN55022.

All I/O cables were positioned to simulate typical usage as per EN55022.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 3 meter away from the EUT as stated in EN 55022. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Analyzer / Receiver quickly scanned from 30MHz to 6000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

The test mode(s) described in Item 3.1 were scanned during the preliminary test:

After the preliminary scan, we found the test mode described in Item 3.1 producing the highest emission level. The EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.

The Analyzer / Receiver scanned from 30MHz to 6000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

The test data of the worst-case condition(s) was recorded.







Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.2.4. TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.2.5 TEST RESULTS

Model No.	PCC2818	Test Mode	full loading
Environmental Conditions	21°C, 55% RH	6dB Bandwidth	120 KHz for 30-1000MHz, 1MHz for 1-6GHz
Antenna Pole	Vertical / Horizontal	Antenna Distance	3m
Detector Function	Peak / Quasi-peak	Tested by	Abner Li

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) – Limits (dB μ V)






Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Please refer to following diagram for individual

PCC2818

Horizontal:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		30.7455	22.43	2.99	25.42	40.00	-14.58	peak		
2		54.2610	28.88	-9.43	19.45	40.00	-20.55	peak		
3		85.2980	36.30	-7.96	28.34	40.00	-11.66	peak		
4	*	133.1511	35.75	-2.72	33.03	40.00	-6.97	peak		
5		207.8501	28.48	-5.10	23.38	40.00	-16.62	peak		
6		426.5210	23.93	-2.43	21.50	47.00	-25.50	peak		





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		31.3992	24.13	2.55	26.68	40.00	-13.32	peak		
2		54.2610	29.26	-9.43	19.83	40.00	-20.17	peak		
3	*	84.7019	35.48	-7.95	27.53	40.00	-12.47	peak		
4		134.0882	28.77	-2.88	25.89	40.00	-14.11	peak		
5		170.1948	24.68	-4.70	19.98	40.00	-20.02	peak		
6		912.8620	21.66	6.39	28.05	47.00	-18.95	peak		





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.3.VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT

7.3.1.LIMITS OF VOLTAGE FLUCTUATION AND FLICKS MEASUREMENT

TEST ITEM	LIMIT	REMARK
P_{st}	1.0	P_{st} means short-term flicker indicator.
P_{lt}	0.65	P_{lt} means long-term flicker indicator.
T_{dt} (ms)	500	T_{dt} means maximum time that dt exceeds 3 %.
d_{max} (%)	4%	d_{max} means maximum relative voltage change.
dc (%)	3.3%	dc means relative steady-state voltage change

7.3.2.TEST INSTRUMENTS

IMMUNITY SHIELDED ROOM				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Harmonic & Flicker Tester	Laplace	AC2000A	311220	2016-08-18
AC Power Source	Sop	PHF-5010	630970	2016-08-18

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.

7.3.3.TEST PROCEDURE

The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under LIGHTING operating conditions.


During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

7.3.4.TEST SETUP



For the actual test configuration, please refer to the related item.

7.3.5.TEST RESULTS

POWER CONSUMPTION	22.5W	Test Results	N/A
ENVIRONMENTAL CONDITIONS	25°C, 55% RH, 996mbar	Limits	Class <input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input checked="" type="checkbox"/> N/A
Test Mode	N/A	Tested by	Abner Li

NOTE:EUT is powered by storage battery,does not apply to the test project.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8 IMMUNITY TEST

8.1. GENERAL DESCRIPTION

Product Standard	EN 55024: 2010	
	Test Type	Minimum Requirement
Basic Standard, Specification, and Performance Criterion required	EN 61000-4-2	Electrostatic Discharge – ESD: 2,4,8kV air discharge, 2,4kV Contact discharge, Performance Criterion B
	EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80 ~1000 MHz, 3V/m, 80% AM(1kHz), Performance Criterion A
	EN 61000-4-4	Electrical Fast Transient/Burst - EFT, AC Power line: 1kV, DC Power line: 0.5kV, Signal line: 0.5kV, Performance Criterion B
	EN 61000-4-5	Surge Immunity Test: 1.2/50 us Open Circuit Voltage, 8 /20 us Short Circuit Current, AC Power Port ~ Line to line: 1kV, Line to ground: 2kV DC Power Port ~ Line to line: 0.5kV, Performance Criterion B
		10/700 us Open Circuit Voltage, Signal Ports and Telecommunication Ports ~ Lines to ground: 4kV Performance Criterion C
	EN 61000-4-6	Conducted Radio Frequency Disturbances Test –CS: 0.15 ~ 80 MHz, 3Vrms, 80% AM, 1kHz, Performance Criterion A
	EN 61000-4-8	Power frequency magnetic field immunity test 50 Hz/60Hz, 1A/m Performance Criterion A
	EN 61000-4-11	Voltage Dips: i) >95% reduction for 0.5 period, Performance Criterion B ii) 30% reduction for 25 period, Performance Criterion C Voltage Interruptions: >95% reduction for 250 period Performance Criterion C





8.2. GENERAL PERFORMANCE CRITERIA DESCRIPTION

Criteria A:	The apparatus shell continues to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the manufacturer does not specify the minimum performance level or the permissible performance loss, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
Criteria B:	<p>After test, the apparatus shell continues to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomenon below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance.</p> <p>During the test, degradation of performance is however allowed. However, no change of operating state if stored data is allowed to persist after the test. If the manufacturer does not specify the minimum performance level or the permissible performance loss, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
Criteria C:	<p>Temporary loss of function is allowed, provided the functions is self-recoverable or can be restored by the operation of controls by the user in accordance with the manufacturer instructions.</p> <p>Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.3. ELECTROSTATIC DISCHARGE (ESD)

8.3.1. TEST SPECIFICATION

Basic Standard:	EN 61000-4-2
Discharge Impedance:	330 ohm
Charging Capacity:	150pF
Discharge Voltage:	Air Discharge: 2,4,8 kV (Direct) Contact Discharge: 2, 4 kV (Direct/Indirect)
Polarity:	Positive & Negative
Number of Discharge:	Minimum 25 times at each test point
Discharge Mode:	1 time/s
Performance Criterion:	B

8.3.2. TEST INSTRUMENT

IMMUNITY SHIELDED ROOM				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Electrostatic Discharge Simulator	Haefely	ONKY 30	175974	2016-08-18

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.3.3. TEST PROCEDURE

The discharges shall be applied in two ways:

a) Contact discharges to the conductive surfaces and coupling planes:

The EUT shall be exposed to at least 200 discharges, 100 each at negative and positive polarity, at a minimum of four test points. One of the test points shall be subjected to at least 50 indirect discharges to the center of the front edge of the **Horizontal Coupling Plane (HCP)**. The remaining three test points shall each receive at least 50 direct contact discharges. If no direct contact test points are available, then at least 200 indirect discharges shall be applied in the indirect mode. Test shall be performed at a maximum repetition rate of one discharge per second.

b) Air discharges at slots and apertures and insulating surfaces:

On those parts of the EUT where it is not possible to perform contact discharge testing, the equipment should be investigated to identify user accessible points where breakdown may occur. Such points are tested using the air discharge method. This investigation should be restricted to those are a Running PC Systemly handled by the user. A minimum of 10 single air discharges shall be applied to the selected test point for each such area.

The basic test procedure was in accordance with IEC 61000-4-2:


- a) The EUT was located 0.1 m minimum from all side of the **HCP** (dimensions 1.6m x 0.8m).
- b) The support units were located another table 30 cm away from the EUT, but direct support unit was/were located at same location as EUT on the HCP and keep at a distance of 10 cm with EUT.
- c) The time interval between two successive single discharges was at least 1 second.
- d) Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- e) Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- f) At least ten single discharges (in the most sensitive polarity) were applied at the front edge of each **HCP** opposite the center point of each unit of the EUT and 0.1 meters from the front of the EUT. The long axis of the discharge electrode was in the plane of the **HCP** and perpendicular to its front edge during the discharge.
- g) At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the **Vertical Coupling Plane (VCP)** in sufficiently different positions that the four faces of the EUT were completely illuminated. The **VCP** (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the EUT.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.3.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the **Ground Reference Plane**. The **GRP** consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A **Horizontal Coupling Plane** (1.6m x 0.8m) was placed on the table and attached to the **GRP** by means of a cable with 940k Ω total impedance representative system as described in section 7 of EN 61000-4-2, and its cables were placed on the **HCP** and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

FLOOR-STANDING EQUIPMENT

The equipment under test was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were isolated from the Ground Reference Plane by an insulating support of 0.1-meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.3.5. TEST RESULTS

Temperature:	23°C	Humidity	53% RH
Pressure	996mbar	Test result	Pass
Test mode	full loading	Test By	Abner Li

PCC2818:

Air Discharge						
Test locations	Test Levels		Results			
	±2,4,8 kV		Pass	Fail	Performance Criterion	Observation
All seams 8Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	B	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2
All coating insulated enclosure 8Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	B	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2

Contact Discharge						
Test Points	Test Levels		Results			
	±2, 4 kV		Pass	Fail	Performance Criterion	Observation
HCP 4Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	B	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2
VCP 4Points	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	B	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2

NOTE: 1. There was no change compared with initial operation during the test.
2. The loss of function of the EUT during the test and it was recovered by itself operation after the test.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.4. RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD (RS)

Basic Standard:	EN 61000-4-3
Frequency Range:	80 MHz ~1000 MHz,
Field Strength:	3 V/m
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of preceding frequency value
Polarity of Antenna:	Horizontal and Vertical
Test Distance:	3 m
Antenna Height:	1.5m
Performance Criterion:	A

8.4.2. TEST INSTRUMENT

966 RS Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Signal Generator	Maconi	2022D	119246/003	2016-08-18
Power Amplifier	M2S	A00181-1000	9801-112	2016-08-18
Power Amplifier	M2S	AC8113/ 800-250A	9801-179	2016-08-18
Power Antenna	SCHAFFNER	CBL6140A	1204	2016-08-18

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.
2. N.C.R.= No Calibration required

8.4.3. TEST PROCEDURE

The test procedure was in accordance with EN 61000-4-3


- The testing was performed in a fully anechoic chamber. The transmit antenna was located at a distance of 3 meters from the EUT.
- The frequency range is swept from 80 MHz to 1000 MHz, with the signal 80% amplitude modulated with a 1kHz sine-wave. The rate of sweep did not exceed 1.5×10^{-3} decade/s, where the frequency range is swept incrementally, the step size was 1% of preceding frequency value.
- The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond.
- The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.4.4. TEST SETUP



For the actual test configuration, please refer to the related item .

NOTE:

TABLETOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of EN 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.4.5. TEST RESULTS

Temperature:	22°C	Humidity	55% RH
Pressure	996mbar	Test result	Pass
Test mode	full loading	Test By	Abner Li

PCC2818:

Frequency (MHz)	Polarity	Position	Field Strength (V/m)	Observation	Result
80 ~ 1000	V&H	Front	3	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2	PASS
80 ~ 1000	V&H	Rear	3	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2	PASS
80 ~ 1000	V&H	Left	3	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2	PASS
80 ~ 1000	V&H	Right	3	Note <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2	PASS

NOTE: 1. There was no change compared with the initial operation during the test.
2. The loss of function of the EUT during the test and it was recovered by itself operation after the test.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.5. ELECTRICAL FAST TRANSIENT (EFT)

8.5.1. TEST SPECIFICATION

Basic Standard: EN 61000-4-4

Test Voltage: AC Power line: 1kV
DC Power line: 0.5kV
Signal line: 0.5kV

Polarity: Positive & Negative

Impulse Frequency: 5 kHz

Impulse Wave-shape: 5/50 ns

Burst Duration: 15 ms

Burst Period: 300 ms

Test Duration: Not less than 1 min.

Performance criterion: B

8.5.2. TEST INSTRUMENT

Immunity Shield Room				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMC PARTNER TRANSIENT 2000	EMC PARTNER	TRA2000	881	2016-08-18
COUPLING CLAMP	EMC PARTNER	H3C	1344012	2016-08-18

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.

2. N.C.R.= No Calibration required

8.5.3. TEST PROCEDURE


- Both positive and negative polarity discharges were applied.
- The length of the "hot wire" from the coaxial output of the EFT generator to the terminals on the EUT should not exceed 1 meter.
- The duration time of each test sequential was 1 minute.
- The transient/burst waveform was in accordance with EN 61000-4-4, 5/50ns.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.5.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The configuration consisted of a wooden table (0.8m high) standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system. A minimum distance of 0.5m was provided between the EUT and the walls of the laboratory or any other metallic structure.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-4 and its cables, were isolated from the Ground Reference Plane by an insulating support that is 0.1-meter thick. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.5.5. TEST RESULTS

Temperature:	23°C	Humidity	51% RH
Pressure	996mbar	Test result	N/A
Test mode	N/A	Test By	Abner Li

NOTE: 1. There was no change compared with initial operation during the test.
 2. The loss of function of the EUT during the test and it was recovered by itself operation after the test.
 3.EUT is powered by storage battery,does not apply to the test project.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.6. SURGE IMMUNITY TEST


8.6.1. TEST SPECIFICATION

Basic Standard:	EN 61000-4-5
Wave-Shape:	Combination Wave 1.2/50 us Open Circuit Voltage 8/20 us Short Circuit Current 10/700 us Open Circuit Voltage
Test Voltage:	AC Power Port ~ Line to line: 1kV, Line to ground: 2kV DC Power Port ~ Line to line: 0.5kV, Signal Ports and Telecommunication Ports ~ Lines to ground: 4kV
Surge Input/Output:	Power Line: L-N/ L-PE / N-PE Telecommunication line: T-Ground / R-Ground
Generator Source Impedance:	2 ohm between networks 12 ohm between network and ground
Polarity:	Positive/Negative
Phase Angle:	0° /90° /180° /270° □
Pulse Repetition Rate:	1 time / min. (maximum)
Number of Tests:	5 positive and 5 negative at selected points
Performance Criterion:	B, C

8.6.2. TEST INSTRUMENT

Immunity Shield Room				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMC PARTNER TRANSIENT 2000	EMC PARTNER	TRA2000	881	2016-08-18
Surge Controller	HAEFELY	Psurge 8000	N/A	2016-08-18
Impulse Module	HAEFELY	PIM 100	N/A	2016-08-18
Coupling Decoupling Filter	HAEFELY	PCD 130	N/A	2016-08-18
Coupling Module	HAEFELY	PCD122	N/A	2016-08-18
Surge Impulse Module	HAEFELY	PIM 120	N/A	2016-08-18
Coupling Module	HAEFELY	PCD 126A	N/A	2016-08-18
Impulse Module	HAEFELY	PIM 110	N/A	2016-06-18

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.





8.6.3. TEST PROCEDURE

a) For EUT power supply:

The surge is applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks was shorter than 2 meters in length.


b) For test applied to unshielded un-symmetrically operated interconnection lines of EUT:

The surge was applied to the lines via the capacitive coupling. The coupling / decoupling networks didn't influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks was shorter than 2 meters in length.

c) For test applied to unshielded symmetrically operated interconnection / telecommunication lines of EUT:

The surge was applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor were not specified. The interconnection line between the EUT and the coupling/decoupling networks was shorter than 2 meters in length.

8.6.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.6.5. TEST RESULTS

Temperature:	23°C	Humidity	53% RH
Pressure	996mbar	Test result	N/A
Test mode	N/A	Test By	Anber Li

NOTE: 1. There was no change compared with initial operation during the test.
 2. The loss of function of the EUT during the test and it was recovered by itself operation after the test.
 3. The function stopped during the test, but can be recoverable manually after the test.
 4.EUT is powered by storage battery,does not apply to the test project.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.7. CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)

8.7.1. TEST SPECIFICATION

Basic Standard: EN 61000-4-6
Frequency Range: 0.15 MHz ~ 80 MHz
Field Strength: 3 V
Modulation: 1kHz Sine Wave, 80%, AM Modulation
Frequency Step: 1 % of preceding frequency value
Coupled cable: Power Mains, Shielded
Coupling device: CDN-M3/2 (2 wires)
Performance criterion: A

8.7.2. TEST INSTRUMENT

CS Test				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Conducted Sensitivity Test System	CDSI	CIT-10/75	126B1246/2013	2016-08-18
CDN	CDSI	CDN M2/M3	2301	2016-08-18
CDN-T8	Schwarzbeck	L801	20100132	2016-08-18
Injection Clamp	EMTEST	F-2031-23MM	9801-112	2016-08-18

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.
 2. N.C.R.= No Calibration required





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.7.3. TEST PROCEDURE

The EUT shall be tested within its intended operating and climatic conditions.


The test shall be performed with the test generator connected to each of the coupling and decoupling devices in turn, while the other non-excited RF input ports of the coupling devices are terminated by a 50-ohm load resistor.

The frequency range was swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80 % amplitude. The signal was modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or the switch coupling devices as necessary. The sweep rate was 1.5×10^{-3} decades/s. Where the frequency range is swept incrementally, the step size was 1 % of preceding frequency value from 150 kHz to 80 MHz.

The dwell time at each frequency was less than the time necessary for the EUT to be exercised, and able to respond. Sensitive frequencies such as clock frequency(ies) and harmonics or frequencies of dominant interest, was analyzed separately.

Attempts was made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.

8.7.4. TEST SETUP



- Note:** 1. The EUT is setup 0.1m above Ground Reference Plane
2. The CDNS and / or EM clamp used for real test depends on ports and cables configuration of EUT.

For the actual test configuration, please refer to the related item .

NOTE:

TABLE-TOP AND FLOOR-STANDING EQUIPMENT

The equipment to be tested is placed on an insulating support of 0.1 meters height above a ground reference plane. All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.7.5. TEST RESULTS

Temperature:	22°C	Humidity	51% RH
Pressure	996mbar	Test result	N/A
Test mode	N/A	Test By	Abner Li

NOTE: 1. There was no change compared with initial operation during the test.
 2. The loss of function of the EUT during the test and it was recovered by itself operation after the test.
 3.EUT is powered by storage battery,does not apply to the test project.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.8. POWER FREQUENCY MAGNETIC FIELD

8.8.1. TEST SPECIFICATION

Basic Standard:	EN 61000-4-8
Frequency Range:	50Hz
Field Strength:	1A/m
Observation Time:	5 minutes
Inductance Coil:	Rectangular type, 1mx1m
Performance criterion:	A

8.8.2. TEST INSTRUMENT

Immunity Shield Room				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power-frequency Magnetic field	SCHAFFNER	CCN 1000-1	72046	2016-08-18
Induction Coil Interface	SCHAFFNER	INA2141	6003	2016-08-18

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.

2. N.C.R.= No Calibration required

8.8.3. TEST PROCEDURE


- The equipment is configured and connected to satisfy its functional requirements. It shall be placed on the GRP with the interposition of a 0.1m-thick insulating support.
- The equipment cabinets shall be connected to the safety earth directly on the GRP via the earth terminal of the EUT.
- The power supply, input and output circuits shall be connected to the sources of power supply, control and signal.
- The cables supplied or recommended by the equipment manufacturer shall be used. 1 meter of all cables used shall be exposed to the magnetic field.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.8.4. TEST SETUP



For the actual test configuration, please refer to the related item .

NOTE:

TABLETOP EQUIPMENT

The equipment shall be subjected to the test magnetic field by using the induction coil of standard dimension (1 m x 1 m). The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

FLOOR-STANDING EQUIPMENT

The equipment shall be subjected to the test magnetic field by using induction coils of suitable dimensions. The test shall be repeated by moving and shifting the induction coils, in order to test the whole volume of the EUT for each orthogonal direction. The test shall be repeated with the coil shifted to different positions along the side of the EUT, in steps corresponding to 50 % of the shortest side of the coil. The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.8.5. TEST RESULTS

Temperature:	22°C	Humidity:	50% RH
Pressure:	996mbar	Test result:	N/A
Test mode:	N/A	Test By:	Abner Li

NOTE: 1. There was no change compared with initial operation during the test.
2. The loss of function of the EUT during the test and it was recovered by itself operation after the test.
3.:EUT is powered by storage battery,does not apply to the test project.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.9. VOLTAGE DIP & VOLTAGE INTERRUPTIONS

8.9.1. TEST SPECIFICATION

Basic Standard:	EN 61000-4-11
Test duration time:	Minimum three test events in sequence
Interval between event:	Minimum 10 seconds
Phase Angle:	0 /45 / 90/ 135/ 180/ 225/ 270/ 315/ 360
Test cycle:	3 times
Performance criterion:	B,C

8.9.2. TEST INSTRUMENT

Immunity shielded room				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMC PARTNER TRANSIENT 2000	EMC PARTNER	TRA2000	881	2016-08-18

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to relevant national and international standards.
2. N.C.R.= No Calibration required

8.9.3. TEST PROCEDURE


1. The EUT and support units were located on a wooden table, 0.8 m away from ground floor.
2. Setting the parameter of tests and then perform the test software of test simulator.
3. Conditions changes to occur at 0 degree crossover point of the voltage waveform.
4. Recording the test result in test record form.





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

8.9.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

8.9.5. TEST RESULTS

Temperature:	24°C	Humidity	54% RH
Pressure	996mbar	Test result	N/A
Test mode	N/A	Test By	Abner Li

- NOTE:** 1. There was no change compared with initial operation during and after the test.
 No unintentional response was found during the test.
 2. The function stopped during the test, but can be recoverable by itself operation after the test.
 3. The function stopped during the test, but can be recoverable manually after the test.
 4. EUT is powered by storage battery, does not apply to the test project.






Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

9 PHOTOGRAPHS OF THE TEST CONFIGURATION

RADIATED EMISSION TEST




ESD TEST





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD TEST





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

10 PHOTOGRAPHS OF EUT

PCC2818

Appearance photograph of EUT



Appearance photograph of EUT





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Appearance photograph of EUT



Appearance photograph of EUT






Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Appearance photograph of EUT




Appearance photograph of EUT






Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Internal photograph of EUT




Internal photograph of EUT





Report No.: WSCT1511003307E Issued: november 25, 2015 Revised: None

Internal photograph of EUT



---- END OF REPORT ----

